

Presentation/Publication Information: APS Meeting, March 11-16, 2001, Seattle, WA

Acknowledgments:

This work was supported under NASA contract [RTOP: 519-40-12(NAS2-14303)].

Abstract:

(Transparencies enclosed)

[K40.042] Coupling of armchair and zigzag tubes to a free electron metal

M. P. Anantram (NASA Ames Research Center, Moffett Field, CA 94035-1000)

The effect of nanotube chirality is of prime importance in determining its electronic properties. We address the issue of how chirality affects the coupling of a nanotube to metal contacts. We model coupling of armchair and zigzag nanotubes to metal contacts, in both the side- and end-contacted geometries. In the side-contacted geometry, the coupling of armchair and metallic-zigzag nanotubes to a free electron metal are significantly different. Namely, it is possible to drive a larger current through a metallic-zigzag nanotube. The predicted difference holds good when both (a) the entire circumference and (b) only a finite sector of the nanotube makes contact to the metal electrode. It might be possible to observe the predicted difference between armchair and zigzag nanotubes using gold contacts.

Which nanowire couples better electrically to a metal contact: Armchair or Zigzag NT?

M. P. Anantram

Nanoelectronics & Device Modeling Group

NASA Ames Research Center

Moffett Field, CA 94035-1000


U. S. A.

Electronic properties of nanotubes are closely related to chirality:

- Metal versus Semiconductor
- Bandgap change with deformation / strain.

Question:


Is there a preferable nanotube chirality to maximize current flow?



Parameters that influence current flow:


- Strength of coupling to metal
- Length of metal-nanotube contact
- Defects
- Metal Fermi wave vector

Transmission vs Energy of a (10,10) Nanotube



- Close to E=0: Total Transmission (T) = 2, Resistance = 6.5 k Ω

Scattering rate



Scattering rate from metal to nanotube (Born approx.):

$$1/\tau \propto | \langle \psi_n | V_{m-nt} | \Phi_m \rangle |^2$$


$$\propto | \langle e^{ik_x L} | e^{ik_x^m L} \rangle |^2 \propto | \langle \Phi | V_{m-nt} | \Phi_m \rangle |^2$$

$$\propto \delta(k_x - k_x^m) \quad | \langle \Phi | V_{m-nt} | \Phi_m \rangle |^2$$

$$\psi = e^{ik_x L} \quad n = \text{integer and } \Phi \text{ is wave func. of atoms in a 1D unit cell}$$

- k_x is conserved
- k_y conservation is relaxed due to finite width of contact area


$$1/\tau \propto \delta(k_x - k_x^m) \quad | < \phi \mid V_m - n \mid \phi_m > |^2$$




ARMCHAIR	ZIGZAG
$E=0$ at $k_x = 2\pi/3a_0 = 0.85 \text{ \AA}^{-1}$ Metal with $k_{Fermi} < 0.85 \text{ \AA}^{-1}$ couples weakly; threshold k_{Fermi}	$E=0$ at $k_x = 0$ No threshold for k_{Fermi}

Below threshold $k_{Fermi} - T$ does not scale with increase in contact length.

ARMCHAIR



ZIGZAG




- threshold for k_F is $\frac{2\pi}{3a_0} = 0.85 \text{ \AA}^{-1}$
(see $k_F = 0.75 \text{ \AA}^{-1}$ and 0.9 \AA^{-1} curves)

no threshold for k_F
(see $k_F = 0.4 \text{ \AA}^{-1}$ curve)

- For zigzag tubes, T_{LM} is small for $k_F \leq 1.2 \text{ \AA}^{-1}$ as a result of the large angular momentum, i.e. armchair tubes couple better than zigzag tubes
- Transmission *increases* with contact length as seen in experiment by Tans et. al., Nature, vol. 386, 474 (1997)

How do we model the system?

- π electron tight binding model
- Metal is modeled as a free electron gas (k_F)



- $T_{RL} + T_{ML} + T_{LL} = 2.$
- Phys. Rev. B, v.58, p. 4882 (1998) and v. 61, p. 14219 (2000)
- Compute self energy due to: (i) metal & (ii) semi-infinite CNT leads


- T is small compared to the maximum possible value of 2.

- Experimentally two possible scenarios are possible to increase T :


* Large contact length - Small coupling




* Small contact length - Large coupling



- Technologically, the second option (right) is better
- Computationally, the second option (right) is less intensive
- We consider a contact length of 30 unit cells (72 \AA for armchair and 125 \AA for zigzag nanotubes), and vary the coupling strength.





- Armchair: Transmission is pinned at values close to unity for metal k_1 of 0.9 and 1.2 \AA^{-1}
- Zigzag: Transmission increases to two (maximum possible value)
- At small coupling strengths, transmission increases more rapidly in the armchair case




Nodes on the cylinder - Shape of NT wave function

$$\psi = e^{imk_x d_0} \phi$$



metal $k_1=0.90 \text{ \AA}^{-1} \rightarrow$ distance between nodes 6 \AA
 Gold $k_1=1.20 \text{ \AA}^{-1} \rightarrow$ distance between nodes 3.4 \AA
 Aluminum $k_1=1.75 \text{ \AA}^{-1} \rightarrow$ distance between nodes 2 \AA

A small sector of the nanotube makes contact to the metal.




Scattering rate from Metal to Nanotube $\propto \langle \phi_{\text{nanotube}} | H_{\text{coupling}} | \psi_{\text{metal}} \rangle$
 $\propto \langle \psi_{\text{metal}} | H_{\text{coupling}} | \phi_{\text{nanotube}} \rangle \sim 0$. Hence, Transmission is pinned close to unity.

- Side-contacted: zigzag nanotube are more desirable (curvature)
- Larger metal Fermi wave vector helps.




Related issues - Future work

- Defects in nanotube (e.g., bond rotation defects)



- Location of metal atoms close to interface (beyond metal jellium)
- Incommensurability of nanotube and metal lattices
- Where are the metal atoms w.r.t. the nanotube atoms.



Conclusions

- Requirement for axial wave vector conservation causes non trivial difference in coupling of zigzag and armchair tubes.

ARMCHAIR

$$\text{cut-off } K_{\text{Fermi}} = 2\pi/3a_0 = 0.85 \text{ \AA}^{-1}$$

ZIGZAG

$$\text{cut-off } K_{\text{Fermi}} = 0$$


- Armchair tubes couple better than zigzag tubes to metal for small lengths of contact or coupling strength

It is desirable for molecular electronics applications to have a small contact area, yet large coupling


The above behavior changes with increase of coupling strength OR contact area, and as a result, the circumferential dependence of the nanotube wave function dictates:

- Transmission in armchair tubes saturates around unity
- Transmission in zigzag tubes saturates at two
- For metal Fermi wave vectors comparable to 1.75 \AA^{-1} the armchair tube couples better to the metal - A direct result of metal-wavefunction modulation over smaller length scales along the circumference of the nanotube.

What happens when the contact length continues to increase? Speculation



How does this compare to: K.L. Choi, J. Ihm, Y.-Q. Yoon & S. Q. Louie, Phys. Rev. B, v. 60 (1999)?



π mode is reflected because of band offset
 π^* mode couples weakly to metal but
leaks out into the metal.

$$\Rightarrow T_{ML} \sim 1, T_{LL} = 1, T_{RL} \sim 0$$

This is different from the present case, where,

$$T_{ML} \sim 1, T_{LL} \sim 0, T_{RL} \sim 1$$

Which nanowire couples better electrically to a metal contact: Armchair or Zigzag NT?


M. P. Anantram
Nanoelectronics & Device Modeling Group
NASA Ames Research Center
Moffett Field, CA 94035-1000
U. S. A.

Electronic properties of nanotubes are closely related to chirality:

- Metal versus Semiconductor
- Bandgap change with deformation / strain.

Question:


Is there a preferable nanotube chirality to maximize current flow?



Parameters that influence current flow:


- Strength of coupling to metal
- Length of metal-nanotube contact
- Defects
- Metal Fermi wave vector

Transmission vs Energy of a (10,10) Nanotube



- Close to $E=0$: Total Transmission (T) = 2, Resistance = 6.5 k Ω

Scattering rate



Scattering rate from metal to nanotube (Born approx.):

$$1/\tau \propto | \langle \psi_n | V_{m-nt} | \Phi_m \rangle |^2$$



$$\propto | \langle e^{ik_x L} | e^{ik_x^m L} \rangle |^2 \propto | \langle V_{m-nt} | \Phi_m \rangle |^2$$

$$\propto \delta(k_x - k_x^m) \quad | \langle \Phi | V_{m-nt} | \Phi_m \rangle |^2$$

$$\psi = e^{ik_x L} \quad n = \text{integer and } \Phi \text{ is wave func. of atoms in a 1D unit cell}$$

- k_x is conserved
- k_y conservation is relaxed due to finite width of contact area


$$1/\tau \propto \delta(k_x - k_x^n) \quad | < \phi | V_{m-nl} | \phi_m > |^2$$




ARMCHAIR	ZIGZAG
$E=0$ at $k_x = 2\pi/3a_0 = 0.85 \text{ \AA}^{-1}$	$E=0$ at $k_x = 0$
Metal with $k_{Fermi} < 0.85 \text{ \AA}^{-1}$ couples weakly; threshold k_{Fermi}	No threshold for k_{Fermi}

Below threshold k_{Fermi} - T does not scale with increase in contact length.

ARMCHAIR




ZIGZAG



- threshold for k_F is $\frac{2\pi}{3a_0} = 0.85 \text{ \AA}^{-1}$ (see $k_F = 0.75 \text{ \AA}^{-1}$ and 0.9 \AA^{-1} curves)
- For zigzag tubes, T_{LM} is small for $k_F \leq 1.2 \text{ \AA}^{-1}$ as a result of the large angular momentum. i.e. armchair tubes couple better than zigzag tubes
- Transmission *increases* with contact length as seen in experiment by Tans et al. Nature, vol. 386, 474 (1997)


How do we model the system?

- π electron tight binding model
- Metal is modeled as a free electron gas (k_F)




- $T_{RL} + T_{ML} + T_{LL} = 2$.
- Phys. Rev. B, v.58, p. 4882 (1998) and v. 61, p. 14219 (2000)
- Compute self energy due to: (i) metal & (ii) semi-infinite CNT leads


- T is small compared to the maximum possible value of 2.
- Experimentally two possible scenarios are possible to increase T :



- Technologically, the second option (right) is better
- Computationally, the second option (right) is less intensive
- We consider a contact length of 30 unit cells (72 \AA for armchair and 125 \AA for zigzag nanotubes), and vary the coupling strength.





- Armchair: Transmission is pinned at values close to unity for metal k_F of 0.9 and 1.2 \AA^{-1}
- Zigzag: Transmission increases to two (maximum possible value)
- At small coupling strengths, transmission increases more rapidly in the armchair case




Nodes on the cylinder - Shape of NT wave function

$$\psi = e^{imk_x a_0} \phi$$



metal $k_F = 0.90 \text{ \AA}^{-1} \rightarrow$ distance between nodes 6 \AA
 Gold $k_F = 1.20 \text{ \AA}^{-1} \rightarrow$ distance between nodes 3.4 \AA
 Aluminum $k_F = 1.75 \text{ \AA}^{-1} \rightarrow$ distance between nodes 2 \AA

A small sector of the nanotube makes contact to the metal.




Scattering rate from Metal to Nanotube $\propto \langle \psi_{\text{nanotube}} | H_{\text{coupling}} | \psi_{\text{metal}} \rangle$
 $\propto \langle \psi_{\text{nanotube}} | \psi_{\text{metal}} \rangle \sim 0$. Hence, Transmission is pinned close to unity.

- Side-contacted: zigzag nanotube are more desirable (curvature)
- Larger metal Fermi wave vector helps.




Related issues - Future work

- Defects in nanotube (e.g., bond rotation defects)



- Location of metal atoms close to interface (beyond metal jellium)
- Incommensurability of nanotube and metal lattices
- Where are the metal atoms w.r.t. the nanotube atoms.



Conclusions

- Requirement for axial wave vector conservation causes non trivial difference in coupling of zigzag and armchair tubes.

ARMCHAIR

$$\text{cut-off } k_{\text{Fermi}} = 2\pi/3a_0 = 0.85 \text{ \AA}^{-1}$$

ZIGZAG

$$\text{cut-off } k_{\text{Fermi}} = 0$$


- Armchair tubes couple better than zigzag tubes to metal for small lengths of contact or coupling strength

It is desirable for molecular electronics applications to have a small contact area, yet large coupling


The above behavior changes with increase of coupling strength OR contact area, and as a result, the circumferential dependence of the nanotube wave function dictates:

- Transmission in armchair tubes saturates around unity
- Transmission in zigzag tubes saturates at two
- For metal Fermi wave vectors comparable to 1.75 \AA^{-1} the armchair tube couples better to the metal - A direct result of metal-wavefunction modulation over smaller length scales along the circumference of the nanotube.

What happens when the contact length continues to increase? Speculation



How does this compare to: H.J. Choi, J. Ihm, Y.-G. Yoon & S.G. Louie, Phys. Rev. B, v. 60 (1999)?



π mode is reflected because of band offset π^* mode couples weakly to metal but leaks out into the metal.

$$\Rightarrow T_{ML}^{-1}, T_{LL}=1, T_{RL}^{-1}$$

This is different from the present case, where,

$$T_{ML}^{-1}, T_{LL}=0, T_{RL}^{-1}$$

Which nanowire couples better electrically to a metal contact: Armchair or Zigzag NT?

M. P. Anantram

Nanoelectronics & Device Modeling Group

NASA Ames Research Center

Moffett Field, CA 94035-1000

U. S. A.

Electronic properties of nanotubes are closely related to chirality:

- Metal versus Semiconductor
- Bandgap change with deformation / strain.

Question:


Is there a preferable nanotube chirality to maximize current flow?



Parameters that influence current flow:


- Strength of coupling to metal
- Length of metal-nanotube contact
- Defects
- Metal Fermi wave vector

Transmission vs Energy of a (10,10) Nanotube



- Close to E=0: Total Transmission (T) = 2, Resistance = 6.5 kΩ

Scattering rate



Scattering rate from metal to nanotube (Born approx.):

$$1/\tau \propto | \langle \psi_n | V_{m-n} | \Phi_m \rangle |^2$$

$$\propto | \langle e^{ik_x L} | e^{ik_x^m} L \rangle |^2 \propto | \langle V_{m-n} | \Phi_m \rangle |^2$$

$$\propto \delta(k_x - k_x^m) \quad | \langle V_{m-n} | \Phi_m \rangle |^2$$

$$\Psi = e^{ik_x L} \quad n = \text{integer and } \Phi \text{ is wave func. of atoms in a 1D unit cell}$$

- k_x is conserved
- k_y conservation is relaxed due to finite width of contact area